

YARDSCRAPERS

TWOSE

フリースタイル用ヤードスクレーパー ¥25万円
of hardwearing rubber blades



トモを引くと
向きが180°変化



フレーム
丈夫です
全面
ゴム
で
覆
い
ま
す

452

ctions

● As 402 but with EXTRA thick very hardwearing rubber blade. Scraping width 1.92m (6'4") to 2.13m (7')



6.3m (21'), 7.2m (24') or 8.1m (27') working widths

- Robust fabricated steel frame
- Large wheels and tyres for fast smooth transport
- Triple sealed bearings
- Transport wheels are well clear of ground and wheel bumpers
- Simple adjustment of rings with cam adjusters
- Pivoting wing sections rolls to follow ground contours
- Transport lock for wing sections

輪が
フリー
で
まわ
ると
油
圧
は
斜
め
に
て



種
→
ヒ
肉
厚
が
4
5
使
用

使いオノオスカーフック 複動1手続
フリーに位置で使用する子とフリーに各リングに軌道
M.F.J.D. N.H. CASE. ルー・ドイスハルカト等。



他ホコ
ハ
ウ
ハ

油圧ニュートラル
シングルバルブ
でレバを操縦して



ガ
で
ま
わ
す

圧を
減
ら
し
て

Castellated Ring Profiles
Castellated rings are unique to Twose and fitted as standard.

The Castellated ring profile has outstanding clod breaking and tilling characteristics to produce a surface seed bed with good capillary action. The castellated profile reduces moisture run off and eliminates mollusc tramways.

牧草、取巻の鎮圧



鎮圧ローラーの名称です。

2003年度価格 160万円

9.4m (30') 10.4m (34') or 12.4m (41') working widths

- Features as 3 section roller plus:
- One double acting ram to convert from transport to working position
 - Double acting ram folds and unfolds each outer section
 - Final folding manoeuvre simply achieved by driving forward

- Safety features:
- Transport and parking lock
 - Valve to control speed at which whole machine can be moved from transport to working position
 - Low centre of gravity for easy and safe transportation

径 61cm
長さ 7.2m
重量 3,805kg

複動1手続



移動中 2.9m

ローラー幅 Rolling Width	6.3m (21')			7.2m (24')				8.1m (27')			9.4m (30')				
Ring Type リングのタイプ	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings	Cambridge Rings	Cambridge Breaker Rings	Large Cambridge Rings			
Diameter of Rings リングの直径	55cm (22")	48cm (19")	55cm (22")	61cm (24")	55cm (22")	48cm (19")	55cm (22")	61cm (24")	55cm (22")	48cm (19")	55cm (22")	61cm (24")			
Weight 重量	3100kg	2900kg	3750kg	3440kg	3400kg	3330kg	4150kg	3805kg	3700kg	3650kg	4245kg	4120kg	4650kg	5775kg	5295kg
Transport Width 移動幅	2.93m (9'7")			2.93m (9'7")				2.93m (9'7")			2.9m (9'6")				
Tyre Size タイヤ径	10.0/75 x 15.3 - 10ply														

¥150万円 ¥160万円 ¥190万円 ¥220万円

Bearings and Axle Diameter: 65mm (2.5")